

DEDICATED MICROS

ice



DM/ICE-DN3U / DM/ICE+DN3XUT 1/3" DAY/NIGHT CAMERAS

- True Day/Night for sensitivity to IR light at night and true colour rendition in daylight
- Unshielded Active Twisted Pair (UTP) video output on Ice+ models allows video signals to be transmitted further than coax cable will allow
- High Resolution 540 lines
- Backfocus thumbwheel for optimum picture quality & ease of setup
- High picture quality due to tailored digital signal processing settings and professional quality optical filters
- Simple to install and configure with a streamlined range of configurable settings
- Accepts C/CS lenses without the need for adapters
- Compatible with all standard auto and manual iris lenses
- Protection against lightning strikes/spikes on power and coax lines
- Diecast zintec casing and cast zinc lens mount for superior build quality
- Compatible with Dennard Housings and Accessories



www.dedicatedmicros.com/baxall

CAMERA FEATURES

FEATURES	DM/ICE-DN3U	DM/ICE+DN3XUT
Sensor	1/3" Sony Super HAD CCD™	1/3" Sony EXview HAD™ CCD
Video Processing	DSP	
Effective Pixels	752 (H) x 582 (V)	
Sensitivity	0.7/ 0.1 lux; for usable picture (40% video) with AGC on; lens at F1.2	0.4/0.1 lux; for usable picture (40% video) with AGC on; lens at F1.2
Resolution	Ultra high resolution 540 TVL	
Video Output	IV p-p composite video via 75Ω BNC connector	<ul style="list-style-type: none"> • IV p-p composite video via 75Ω BNC connector • Unshielded Twisted Pair (UTP) video output
Signal to Noise Ratio	Better than 50dB	
Auto White Balance	2,500K ~ 9,500K	2,500K ~ 9,500K / Manual
AGC	On / Off, max <28dB	On/Off, Low/High, max < 28dB
Electronic Iris	1/50s~1/100,000s; On/ Off	1/50s~1/100,000s; On / Off
Backlight Compensation	On/Off	On/Off, centre weighted, 7 user selectable windows
Gamma Correction	0.45	0.45/1.0
Synchronisation System	Internal or Line lock (±180° adjustment)	
Additional Features	<ul style="list-style-type: none"> • User selectable day/night threshold settingΣ • External D/N Contact 	<ul style="list-style-type: none"> • Day/ Night High/ Low - user selectable day/night threshold setting • External D/N contact • Sharpness On/ Off • Digital Record Mode - to reduce bandwidth or storage requirements • Pk White Inversion • Pk White Inversion Threshold Pot • Manual white balance (push set) • Unshielded Twisted Pair (UTP) video output option • Rotary BCD Shutter


DM/ICE-DN3U / DM/ICE+DN3XUT

SPECIFICATIONS


Lens Options	
Lens Mount and Focus	'C' or 'CS' mount, thumbwheel adjustment
Auto Iris Lens	DC and Video via 4 pin socket
Direct Drive (DC iris)	4-pin square type socket on the side of the camera. DC level is user defined via a potentiometer located on the rear of the camera
Power Supply	
Low Voltage Source / L version	AC: 24V ±15% @50Hz DC: 12V -10% +15%
Mains Source / M version	98~260V AC 50Hz
Consumption	Less than 4.2W including 50mA DC lens
Input Connector	/L: 2-way terminal connector on rear panel /M: 2m twin conductor mains cord (Class 2 product)
Power Indicator	Blue LED on rear panel
Mechanical	
Camera Mount	1/4" 20 UNC top and bottom
Dimensions (mm)	131 (L) x 63 (H) x 62 (W)
Weight	/L: 0.4kg, shipping weight 0.53kg /M: 0.52kg, shipping weight 0.62kg
Material	Cast Zinc lens mount; zintec case; V0 ABS trim
Environmental	
Operating Temperature	-10 to +50°C (14 to 122°F)
Operating Humidity	20% to 80% relative humidity, non condensing
Storage Temperature	-10 to +70°C (14 to 158°F)
Storage Humidity	20% to 90% relative humidity, non condensing
1/3" Day / Night Cameras	
DM/ICE-DN3U/M	1/3" Ultra Resolution Day/Night, 540 TVL, 0.7 lux (Colour), 0.1 LUX (Mono), C/CS , AI/DD/EI, 98-260V, 131x63x62mm
DM/ICE-DN3U/L (N)	1/3" Ultra Resolution Day/Night, 540 TVL, 0.7 lux (Colour), 0.1 LUX (Mono), C/CS , AI/DD/EI, 12/24V, 131x63x62mm
DM/ICE-DN3XUT/M	1/3" Ultra Resolution Day/Night, 540 TVL, 0.4 lux (Colour), 0.1 LUX (Mono), C/CS , AI/DD/EI, Peak White Inversion, 98-260V, 131x63x62mm
DM/ICE-DN3XUT/L	1/3" Ultra Resolution Day/Night, 540 TVL, 0.4 lux (Colour), 0.1 LUX (Mono), C/CS , AI/DD/EI, Peak White Inversion, 12/24V, 131x63x62mm

(N) NTSC version available


DM/ICE-DN3U DM/ICE+DN3XUT




DM/ICE-DN3U/L



DM/ICE-DN3U/M



DM/ICE+DN3XUT/L



DM/ICE+DN3XUT/M

- Dedicated Micros UK** 1200 Daresbury Park, Daresbury, Warrington, WA4 4HS - Tel: +44 (0) 845 600 9500 Fax: +44 (0) 845 600 9504
- Dedicated Micros USA** 14434 Albemarle Point Place, Suite 100, Chantilly, Virginia 20151 - USA Freephone: 800 864 7539
Tel: +1 703 904-7738 Fax: +1 703 904-7743
- Dedicated Micros Germany** Neckarstraße 15, 41836 Hückelhoven, Germany - Tel: +49 243 352 580 Fax: +49 24 33 52 58 10
- Dedicated Micros France** 9-13 rue du Moulinet, 75013 Paris, France - Tel: +33 1 45 81 99 99 Fax: +33 1 45 81 99 89
- Dedicated Micros Benelux** Joseph Chantraineplantsoen 1, 3070 Kortenberg, Belgium - Tel: +32 2751 3480 Fax: +32 2751 3481
- Dedicated Micros Russia** Russia, CIS and Baltic States Tel: +7 495 9259906 Fax: +7-495-6586769
- Dedicated Micros Slovenia** Delavska cesta 24, 4208 Sencur, Slovenia - Tel: +386 4 279 18 90 Fax: +386 4 279 18 91
- Dedicated Micros Australia** 2/9 Packard Avenue, Castle Hill, NSW 2154, Australia - Tel: +612 9634 4211 Fax: +612 9634 4811
Master Licence 404588736
- Dedicated Micros New Zealand** 4/36 William Pickering Drive, Albany, Auckland 0663, New Zealand - Freephone: 0800 364 276
Tel: +64 448 2366 Fax: +64 (09) 448 2369
- Dedicated Micros Malta** BLB017, Bulebel Industrial Estate, Zejtun, ZTN3000, Malta - Tel: +356 21483 673/4 Fax: +356 21449 170
- Dedicated Micros Asia** 16 New Industrial Road, #03-03 Hudson TechnoCentre, Singapore 536204 - Tel: +65 62858982 Fax: +65 62858646
- Dedicated Micros Middle East** Building 11, Suite 405-407, PO Box 500291, Dubai Internet City, Dubai, United Arab Emirates
Tel: +971 (4) 390 1015 Fax: +971 (4) 390 8655
- Dedicated Micros India** A/8/7 & A/8/8, Groma House, Plot No 14C, Sector 19, Vashi Navi Mumbai Pin Code : 400703 Tel: +91 98214 58333

Super HAD CCD™ is a trademark of the Sony Corporation. Price and specification are subject to change without notice.